

**TSM** cubicle track is provided with track, carriers, gates, stops and splices included. Curtains are available separately. Surface mounted track can be mounted directly onto finished ceiling, or recessed. Fastening of the track is to be made 36" on center (914mm) with #8 pan head screws or toggle bolts (fasteners not included).

Dual channel extruded aluminum track has a baked white enamel finish. Track dimensions are  $1^{3}/8" \times 3^{4}$ " deep x .062" wall ( $35 \times 19 \times 1.7$ mm). Track carriers are designed for fast, unimpeded movement; axle and wheel are virgin nylon, bead chain is nickel-plated brass and hook assembly is polished aluminum.

Curtains are flame-resistant, stain-resistant, anti-bacterial vinyl fabric with polyester reinforcement. Curtains include a 21" (533mm) high nylon mesh for sprinkler clearance as well as ventilation and light.

There is a 2<sup>1</sup>/<sub>2</sub>" clearance from the ceiling to the top of the curtain. Curtains should hang 9" -15" above finished floor. Contact the factory for custom curtain sizes.

## Track and Accessories

#### K Straight

BICLE

Straight Track

Track only. Order gates, carriers, splices and stops separately.

K-2 - 2' (610mm) K-3 - 3' (914mm) K-4 - 4' (1219mm) K-5 - 5' (1524mm)	<b>K-6</b> - 6' (1829mm) <b>K-7</b> - 7' (2134mm) <b>K-8</b> - 8' (2438mm)
<b>K-J</b> -J (132411111)	





#### K-8 Set Straight Track

Includes 8' track, one gate, one stop and 15 carriers.

### KE-22

#### Elbow Track

Includes track, nine carriers & two splices. 24" x 24" (610 x 610mm) 90° Elbow with 12" Bend Radius (305mm)





#### KC Cubicle Track Curtains

Specify curtains at least 10% wider than track. Heights include nylon mesh.

WHITE	ALMOND	Height and Width	# of K-Hooks Req'd
KC745-WH	KC745-ALM	7' High x 4 <sup>1</sup> /2' Wide (2134x114mm)	9
KC760-WH	KC760-ALM	7' High x 6' Wide (2134x1829mm)	12
KC775-WH	KC775-ALM	7' High x 7 <sup>1</sup> /2' Wide (2134x2286mm)	16
KC790-WH	KC790-ALM	7' High x 9' Wide (2134x2743mm)	18
KC845-WH	KC845-ALM	8' High x 4 <sup>1</sup> /2' Wide (2438x114mm)	9
KC860-WH	KC860-ALM	8' High x 6' Wide (2438x1829mm)	12
KC875-WH	KC875-ALM	8' High x 7 <sup>1</sup> /2' Wide (2438x2286mm)	16
KC890-WH	KC890-ALM	8' High x 9' Wide (2438x2743mm)	18

# Closet Rods



Shelf not included.

#### DB-1

Closet Shelf Bracket Chrome plated steel.  $11\frac{1}{10}$ " wall to centerline of rod x  $10\frac{1}{10}$ " high (295 x 276mm).

Up to 6' Lengths Require 2 Brackets Lengths between 6'-9' Require 3 Brackets Lengths between 9'-12' Require 4 Brackets

**CQ Closet Rod Tubing CQ-6** - 6' (1829mm) **CQ-12** - 12' (3658mm) TSM will cut to fit as specified. 1 <sup>5</sup>/16" O.D. x .080" Chrome plated steel.



#### **DF-Set**

Includes one each DF-1 and DF-2. Both flanges are chrome plated brass,  $2\sqrt[3]{4}$ " round x  $\sqrt[7]{4}$ " high (70 x 22mm).





DF-1 Closet Rod Flange DF-2 Closet Rod Saddle

Flange Clos



TUBULAR SPECIALTIES MFG. 800/GrabBar (800/472-2227) • Fax: 310/217-0653